

Smiljanic 2000-0230

IN THE CLAIMS:

**1. (Currently Amended)** A method of allocating bandwidth for use at a packet switch having a plurality of inputs for switching to specified outputs and a plurality of corresponding input buffers having input-output queues and associated counters, said method comprising the steps of

- dividing time into a plurality of frames of time slots, each frame having a specified integer value of time slots;
- loading said counters associated with said input-output queues to said a negotiated integer value once per said frame;
- said inputs sequentially selecting available said outputs to which said inputs send packets in specified future time slots, wherein priority is given to those of input-output queues with whose associated ones of said counters have having positive values;
- said selection of outputs by said inputs being done by using a pipeline technique, wherein a schedule is calculated within multiple time slots, wherein schedules for multiple future time slots being calculated in each time slot; and
- decrementing said counters of selected queues by 1.

**2. (Currently Amended)** A method of allocating bandwidth in a circuit switch having a plurality of inputs for switching to outputs, input tables and input-output counters, said method comprising the steps of:

- dividing time into a plurality of (data) frames comprising (data) time slots, and reservation frames comprising reservation time slots, each frame having a specified number of time slots;
- loading said counters to the difference between the current total number of negotiated credits and the total number of released credits in the a previous reservation frames of said reservation frames;
- said inputs sequentially releasing ~~the~~ time slot reservations for outputs if their corresponding counters are have negative values;
- said inputs sequentially reserving time slots for unreserved outputs if their corresponding counters are have positive values;

Smiljanic 2000-0230

whenever said input releases an output, the corresponding counter is incremented by 1, and whenever said input releases reserves an output the corresponding counter is decremented by 1;

said input tables being updated after all inputs have had a chance to release and reserve outputs for future time slots, storing outputs reserved in each time slot of a frame, and outputs reserved by the corresponding input in each time slot of a frame; and

~~said release, reservation~~ releasing of time slot reservations, reserving of time slots, and table update of outputs by said inputs being done using a pipeline technique, wherein a schedule is calculated within multiple reservation time slots, and schedules for multiple future time slots are calculated in each reservation time slot.

**3. (Original)** The method of claim 1, comprising a pipeline technique where input  $i$ ,  $i = 0, 1, \dots, N-1$  chooses output for time slot  $k$  in time slot  $k - \lceil (N-i)/p \rceil$  where  $p$  is the number of selections made in one time slot, and  $\lceil x \rceil$  is the smallest integer greater or equal to  $x$ .

**4. (Previously Presented)** The method of claim 1, comprising a pipeline technique where input  $i$ ,  $i=0, 1, \dots, N-1$ , chooses an output from group of outputs  $l$ ,  $l=0, 1, \dots, p-1$ , for time slot  $k$  in time slot  $k - ((N-i)*p-l)$  where  $p$  is the number of time slots required for one selection.

**5. (Original)** The method of claim 2, comprising a pipeline technique where input  $i$  releases output for time slot  $k+mF$ ,  $m=1, 2, \dots$  in time slot  $\lceil k - (2N-i)/p \rceil$ , and input  $i$  chooses output for time slot  $k+mF$ ,  $m=1, 2, \dots$  in time slot  $\lceil k - (N-i)/p \rceil$ , where  $p$  is the integer ratio of the time slot duration and the reservation time slot duration, and  $\lceil x \rceil$  is the smallest integer greater or equal to  $x$ .

**6. (Previously Presented)** The method of claim 2, comprising a pipeline technique where input  $i$ ,  $i=0, 1, \dots, N-1$  releases an output from group of outputs  $l$ ,

Smiljanic 2000-0230

$l=0,1,\dots,p-1$ , for time slot  $k+mF$ ,  $m=1,2,\dots$  in time slot  $k - ((N-i)*p-l) - Np$ , and input  $i$  chooses an output from group of outputs  $l$  for time slot  $k+mF$ ,  $m=1,2,\dots$  in time slot  $k - ((N-i)*p-l)$  where  $p$  is the ratio of the durations of the reservation time slot and (data) time slot.

7. (Original) The method of claim 2, comprising a pipeline technique wherein input table  $i$  is finally updated  $N$  reservation time slots after it reserved the output.

8. (Currently Amended) The method of claims 3 and or 5, wherein input  $i$  loads its counters in time slot  $k * F + 1 - \lceil (N-i) / p \rceil$ .

9. (Currently Amended) The method of claims 4 and or 6, wherein input  $i$  loads its counters for group of outputs  $l$  in time slot  $k * F + 1 - ((N-i) * p - l)$ .

10. (Original) The method of claim 2, comprising a pipeline technique where input  $i$  releases output for time slot  $k+nF+mpF$ ,  $k < F$ ,  $m, n=1,2,\dots$  in reservation time slot  $(m-1)F+k-(2N-i)$ , and input  $i$  chooses output for time slot  $k+nF+mpF$ ,  $m, n=1,2,\dots$  in reservation time slot  $(m-1)F+k-(N-i)$  where  $p$  is the integer ratio of the reservation time slot duration and the time slot duration.

11. (Original) The method of claim 10, wherein input  $i$  loads its counters in reservation time slot  $(m-1)F+1-(2N-i)$ .

12. (Currently Amended) The method of claim 1 and or 2 further comprising the step of negotiating values of time slots per frame associated with input-output pairs, wherein input-output pair  $(i,j)$  can be allocated additional  $\Delta a_{ij}$  time slots per frame of length  $F$  if it holds that:

$$\sum_m a_{im} + \sum_m a_{mj} - a_{ij} + \Delta a_{ij} \leq F,$$

Smiljanic 2000-0230

where  $a_{kl}$ ,  $0 \leq k, l \leq N-1$ , is the number of time slots previously assigned to input-output pair  $(k, l)$ , and  $N$  is the number of inputs and outputs.

**13. (Currently Amended)** The method of claim 1 and or 2 further comprising the step of negotiating values of time slots per frame associated with input-output pairs, wherein input-output pair  $(i, j)$  can be allocated additional  $\Delta a_{ij}$  time slots per frame of length  $F$  if it holds that:

$$\sum_m a_{im} + \Delta a_{ij} \leq (F+1)/2, \quad \sum_m a_{mj} + \Delta a_{ij} \leq (F+1)/2,$$

where  $a_{kl}$ ,  $0 \leq k, l \leq N-1$ , is the number of time slots previously assigned to input-output pair  $(k, l)$ .

**14. (Currently Amended)** The method of claim 1 and or 2 further comprising the step of updating the number of credits per frame assigned to input-output pair, when its bandwidth request is accepted, or when it releases previously reserved bandwidth:

$$a_{ij} \leftarrow a_{ij} + \Delta a_{ij}.$$

**15. (Currently Amended)** The method of claims 12 and or 13 wherein steps 3 and 4 of bandwidth allocation the claim 1 method  $[[1]]$  are replaced with any maximal matching algorithm, wherein maximal matching algorithm is the one in which either input will transmit packet or receiver will receive packet in some time slot if there is at least one packet from said input to the said output.

**16. (Currently Amended)** The methods of claims 12 and or 13 wherein steps 3 and 4 of the claim 1 method  $[[1]]$  are replaced with the previously proposed parallel iterative matching algorithm (PIM) which is maximal matching algorithm defined in claim 15.

**17. (Previously Presented)** The method of claim 13 wherein applied to the bandwidth allocation in wide area network, wherein switches in wide area network advertise to other switches reserved bandwidth on all its input and output links:

Smiljanic 2000-0230

$$B_i \sum_m a_{im} / F, \quad B_j \sum_m a_{mj} / F, \quad 0 \leq i, j \leq N-1,$$

where  $B_i, B_j$  are bit-rates of the corresponding links. When new bandwidth  $\Delta B$  is requested between two nodes in the network, then all links for which:  $\Delta B > B_j / 2 - B'_i$ , are excluded from the network if  $B_i$  is the link bit-rate, and  $B'_i$  is the link reserved bit-rate (bandwidth), and bandwidth is reserved according to any routing protocol (such as OSPF) using remaining links from the source to the destination.

**18. (Currently Amended)** The method of claim 1 implemented for short packet transmission time  $T$  wherein new bandwidth can be allocated fast by using the methods of claims 12 and or 13 within  $FT$  even for long frames lengths  $F$ , wherein one time slot per frame guarantees bandwidth of  $B/F$  by using the methods of claims 12 or 13, where  $B$  is the line bit-rate and minimum guaranteed bandwidth can be made low by increasing  $F$ .

**19. (Currently Amended)** An apparatus for allocating bandwidth for use at a packet switch having a plurality of inputs for switching to specified outputs and a plurality of corresponding input buffers having input-output queues, said buffers being coupled to said input-output and having associated counters, said method comprising the steps of:

time division means for dividing time into a plurality of frames of time slots, each frame having a negotiated integer value of time slots;

loading means for loading said counters associated with said input-output queues to said negotiated integer value once per said frame;

wherein said inputs sequentially selecting available said outputs to which said inputs send packets in specified future time slots, wherein priority is given to input-output queues with positive counters having positive values;

and wherein selection of outputs by said inputs is done using a pipeline technique, and wherein not all inputs select outputs for a specified time slot in the future while other inputs choose outputs for some other future time slots.

**20. (Original)** The apparatus of claim 19 further including means for negotiating values of time slots per frame associated with input-output pairs, wherein

Smiljanic 2000-0230

input-output pair  $(i,j)$  can be allocated additional  $\Delta a_{ij}$ , time slots per frame of length  $F$  if it holds that:

$$\sum_m a_{im} + \sum_m a_{mj} - a_{ij} + \Delta a_{ij} \leq F,$$

where  $a_{kl}$ ,  $0 \leq k, l \leq N-1$ , is the number of time slots previously assigned to input-output pair  $(k,l)$ , and  $N$  is the number of inputs and outputs.

**21. (Original)** The apparatus of claim 20 further including negotiating means for negotiating values of time slots per frame associated with input-output pairs, wherein input-output pair  $(i,j)$  can be allocated additional  $\Delta a_{ij}$  time slots per frame of length  $F$  if it holds that:

$$\sum_m a_{im} + \Delta a_{ij} \leq (F+1)/2, \quad \sum_m a_{mj} + \Delta a_{ij} \leq (F+1)/2,$$

where  $a_{kl}$ ,  $0 \leq k, l \leq N-1$ , is the number of time slots previously assigned to input-output pair  $(k,l)$ .

**22. (Currently Amended)** A method of exchanging the information through a packet switch having a plurality of inputs for switching to specified outputs and a plurality of corresponding input buffers having input-output queues and associated counters, said method comprising the steps of:

attaching users to each input/output port so that their total transmission and reception capacities is less than a half of the port capacity;

prior to sending packets sources check the available reception capacity of the destination and transmits packets to it not exceeding this capacity;

packets are schedules in a switch according to the maximal matching algorithm as defined in claim 15[[:]].

**23. (Previously Presented)** A method of claim 22 wherein the maximal matching algorithm in step 3 is the algorithm in which inputs sequentially select outputs, and which may be implemented by using a pipeline technique as defined in claim 1.